



VENOM POWER

Pro Chargers & Accessories

SINCE 2001

Venom power, a leading American brand since 2001, specializes in high-performance rechargeable power solutions for FPV drones, payload and long-range UAVs, and RC applications.

Trusted by professionals, hobbyists, and commercial operators worldwide, Venom Power delivers Grade A reliability and precision-engineered power systems that push performance boundaries in every flight and drive.

Our Product Portfolio Includes:

Drone Pro LiPo Series

High-discharge power for FPV drones and payload UAVs.

Drone Endurance Semi-Solid Series

High energy density and capacity for long-range UAVs.

RC Fly LiPo Series

Optimized for RC helicopters and fixed-wing airplanes.

RC Drive LiPo Series

Engineered for RC on-road cars, off-road vehicles, and marine models.

RX/TX Packs & NiMH Series

RX/TX Packs, and cost-effective solutions for entry-level RC hobbyists.

Pro Chargers & Accessories

Professional-grade charging systems and adaptive power solutions.



Pro Chargers & Accessories

Venom Power Pro Quad 4-Port AC/DC Battery Charger (6S/7A/100W x 4)



Dimension	L178*W108*H235mm
Display Type	LCD
Charge Current	0.1–7.0A x 4
Discharge Rate	0.1–1.0A
Circuit Power	100W x 4 Ports
Input	DC 11.0V-18.0V / AC 100V-240V
USB Output	5V 2.3A USB 2.0 x 4
Current Drain Balancing	300mAh per Cell
Supported Battery Packs	LiPo 1~6S, LiHV 1~6S, Li-ion 1~6S, LiFe 1~6S, NiMH/NiCD 1~15S, Pb 1~10S
Included Charge Leads	EC3, EC5, XT60, HXT 4, JST, Deans, Tamiya, Alligator, Receiver (RX)

Venom Power Pro Duo 2-Port AC/DC Battery Charger (6S/7A/80W x 2)



Dimension	L127*W56*H136mm
Display Type	LCD
Charge Current	0.1-7.0A x 2
Discharge Rate	0.1-1.0A
Circuit Power	80W x 2 Ports
Input	DC 11.0V-18.0V / AC 100V-240V
USB Output	5V 2.3A USB 2.0 x 2
Current Drain Balancing	300mAh per Cell
Supported Battery Packs	LiPo 1~6S, LiHV 1~6S, Li-ion 1~6S, LiFe 1~6S, NiMH/NiCD 1~15S, Pb1~10S
Included Charge Leads	EC3, EC5, XT60, HXT 4, JST, Deans, Tamiya, Alligator, Receiver (RX)

Venom Power Pro 4 AC Sport Balance Charger (4S/6A/60W)

Dimension	L115*W100*H50mm
Display Type	LCD
Charge Current	0.1A-6.0A
Discharge Rate	0.1A-2.0A (10W)
Circuit Power	60W
Input	AC 100V-240V
Current Drain Balancing	300mAh per Cell
Supported Battery Packs	LiPo 2~4S, LiHV 2~4S, Li-ion 2~4S, LiFe 2~4S, NiMH/NiCD 6~8S, Pb 3~6S
Included Charge Leads	EC3, XT60



Venom Power AC/DC Lipo Battery Balance Charger (4S/3A/40W)



Dimension & Weight	L130*W143*H49mm, 306g
Display Type	LCD
Charge Current	0.1-3.0A
Balance Port Type	JST-XH
Circuit Power	40W
Input	DC 10.0-18.0V / AC 100V-240V
Supported Battery Packs	LiPo 2~4S, Li-ion 2~4S, LiFe 2~4S

Notes

We offer flexible battery pack solutions—configured with our standard cells or fully customized to your specifications, available for bulk orders. Partner with us under the Venom brand, ODM/OEM private labeling, or co-branding collaborations.